

# Technical Data Sheet

## Permacron<sup>®</sup> Antisilicone 8510

Permacron<sup>®</sup> Antisilicone 8510 can be added to Permacron<sup>®</sup> and Permasolid<sup>®</sup> Clear Coats to avoid fisheyes on contaminated surfaces.

This product is for professional painting of vehicles only.




Technical Data Sheet No. 990.5. Apr. 2011

Copyright© 2011 DuPont. Spies Hecker<sup>®</sup>, Raderal<sup>®</sup>, Permacron<sup>®</sup>, Permahyd<sup>®</sup>, Permasolid<sup>®</sup>, Priomat<sup>®</sup>, and Permaloid<sup>®</sup> are registered trademarks of E.I. du Pont de Nemours and Company for its brands of refinish systems. All rights reserved.

**Use:** Additive for 2K acrylic top coats in the event of fish eyes.  
If fish eyes occur when starting to apply the clear coat, Permacron® Antisilicone 8510 may be added to the ready to spray mixture.

### Mixing:



Add 1 cap = 25 ml (5% by volume) Permacron® Antisilicone 8510 to 500 ml (approx. 17 oz.) of ready to spray 2K clear coat and mix well.

### Special Notes:

1. Permacron® Antisilicone 8510 is not recommended as a preventative measure.
2. Permacron® Antisilicone 8510 must never be added to base coats or primers and surfacers.
3. Clean equipment thoroughly immediately after use.

### Important Regulatory Information

Please see the appropriate VOC wall chart for compliance for your area. The values depicted below are "ready to spray."

VOC Category	VOC Regulatory and Actual	Density g/l	Wt% Volatiles, Water & Exempts	Vol% Water & Exempts
Specialty Coating Fisheye Eliminator	846 g/l, 846 g/l	868 g/l	97.5% 0.0%, 0.0%	0.0%

- **For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and MSDS precautions. If mixed with other components, mixture will have hazards of all components. Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates. Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.**
- Any analytical results set forth herein do not constitute a warranty of specific product features or of the product's suitability for a specific purpose. All products are sold pursuant to our general conditions of sale. We hereby disclaim all warranties and representations, express or implied, with respect to this product, including any warranty of merchantability or fitness for a particular purpose. This product is protected by patent law, trademark law, copyright law, international treaties and/or other applicable law. All rights reserved. Unauthorized sale, manufacturing or use may result in civil and criminal penalties.

SPIES HECKER, INC.  
47818 West Anchor Court  
Plymouth, MI 48170  
Tel. 800-447-7437 (800-44-SPIES)  
Fax 734-354-3405  
[www.SpiesHeckerUSA.com](http://www.SpiesHeckerUSA.com)

